

# TiM5xx Complete measurement accuracy



**2D LIDAR SENSORS** 



#### Technical data overview

recrinical data overview			
Application	Indoor / Outdoor (depending on type)		
Measurement principle	HDDM <sup>+</sup> / HDDM (depending on type)		
Integrated application	Output of measurement data		
Aperture angle			
Horizontal	270°		
Angular resolution	1° 0.33°		
Working range	0.05 m 25 m (depending on type)		
Scanning range			
At 10% remission	2 m 8 m (depending on type)		
Scanning frequency	15 Hz		
Ambient operating temperature	–25 °C +50 °C $^{1)}$ (depending on type)		
Serial	✓		
USB	✓		
Ethernet	1		
Digital inputs	0		
Digital outputs	1 (PNP, "SYNC"/"device ready")		
Weight	150 g / 250 g (depending on type)		

<sup>1)</sup> IEC 60068-2-14:2009.

#### **Product description**

More than just object detection: The TiM5xx 2D LiDAR sensor is a non-contact ranging solution within the TiM series from SICK. Thanks to its HDDM technology, the TiM5xx is able to monitor large areas in indoor and outdoor applications – regardless of the surface or ambient light. Enclosed in a compact, rugged housing, the TiM5xx provides accurate measurement data from the scanned surface, making it possible to determine additional information such as the size and shape of objects. The TiM5xx is flexible for use in a variety of industrial applications as well as in building automation. The integrated Ethernet interface makes for easy implementation and remote maintenance. The TiM5xx is an efficient solution for stationary use as well as for use on automated guided vehicles (AVG) and in other mobile applications.

#### At a glance

- Monitoring area of up to 1,470 m<sup>2</sup> with just one sensor
- · High ambient light tolerance due to HDDM technology
- Rugged housing with up to an IP 67 enclosure rating
- Low power consumption (typ. 4 W)
- · Compact design with a housing height of just 86 mm maximum
- Integrated Ethernet interface
- Long sensing range of up to max. 25 m
- Industry-standard design and M12 male connector

## Your benefits

- · Reliable object detection independent of the surface and ambient light
- IP 67 enclosure rating can be relied upon to withstand both indoor and outdoor conditions
- · Easy integration into compact automated guided vehicles (AGV) due to small size
- Ethernet interface makes for easy implementation and remote maintenance
- Can determine additional information such as object size, shape, etc. through measurement data output
- Low implementation costs due to scalability: Sensor telegram is identical to sensor telegrams for 2D LiDAR sensors in the SICKportfolio

### Fields of application

- Collision avoidance for automated guided vehicles (AGV)
- Object measurement and detection
- Monitoring of objects in the field of building automation
- Pallet detection
- Navigation of automated guided vehicles (AGV)

### Ordering information

Other models and accessories → www.sick.com/TiM5xx

- Application: Indoor
- Integrated application: output of measurement data
- Working range: 0.05 m ... 4 m

Angular resolution	Digital outputs	Connection type	Measure- ment principle	Туре	Part no.
1°	1 (PNP, "SYNC"/"de- vice ready")	1 x cable with 12- pin M12 male con- nector (0,3 m) 1 x Micro USB female connector, type B	HDDM <sup>+</sup>	TIM510- 9950000S01	1062210

- Application: Outdoor
- Integrated application: output of measurement data
- Digital outputs: 1 (PNP, "SYNC"/"device ready")

Working range	Angular resolution	Connection type	Measure- ment principle	Туре	Part no.
0.05 m 10 m	0.33°	1 x "Ethernet" con- nection, 4-pin M12 female connector 1 x connection "Pow-	HDDM	TIM561- 2050101S80	1106065
			HDDM <sup>+</sup>	TiM561-2050101	1071419
	10	er/Synchronization output" 5-pin, M12	HDDM <sup>+</sup>	TIM551-2050001	1060445
0.05 m 25 m	0.33°	male connector 1 x Micro USB female connector, type B	HDDM	TiM571-2050101	1075091
			HDDM <sup>+</sup>	TiM581-2050101	1099504
		1 x "Ethernet" connec- tion, cable, with RJ45 male connector (1 m) 1 x "Power/Synchro- nization output" con- nection, 5-wire cable with open end (1 m) 1 x Micro USB female connector, type B	HDDM	TiM571- 9950101S01	1079742

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

