

DOL-MS10-G30MMA2

Sensor/actuator cable

PLUG CONNECTORS AND CABLES





Ordering information

Туре	Part no.
DOL-MS10-G30MMA2	7102135

Other models and accessories → www.sick.com/Sensor_actuator_cable

Detailed technical data


Technical specifications

Connection type head A	Female connector, MS/10, 10-pin, straight
Connection type head B	Flying leads
Cable	30 m, 11-wire
Cable diameter	7.5 mm
Conductor cross section	4 x 2 x 0.25 mm2 + 2 x 0.5 mm2 + 1 x 0.14 mm ²
Shielding	Shielded

Classifications

ECLASS 5.0	19030312
ECLASS 5.1.4	19030312
ECLASS 6.0	27060304
ECLASS 6.2	27060304
ECLASS 7.0	27060304
ECLASS 8.0	27060304
ECLASS 8.1	27060304
ECLASS 9.0	27060304
ECLASS 10.0	27060304
ECLASS 11.0	27060304
ECLASS 12.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249
ETIM 8.0	EC003249
UNSPSC 16.0901	26121604

Dimensional drawing (Dimensions in mm (inch))



① Length of cable

PIN	Wire color	Function
A	White	A
В	Pink	В
С	Purple	M
D	Red	+V _S
Е	Orange	Set zero pulse
F	Blue	GND
G	Green	D-Sub GND
Н	Brown	A-
I	Black	B-
J	Yellow	M-

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

